

Reihe 3

Verfahrenstechnik

Nr. 952

M.Sc. Xiao Zhao,  
Xinjiang

## Reactor network synthesis with guaranteed robust performance

Berichte aus der  
Aachener Verfahrenstechnik - Prozesstechnik

RWTH Aachen University



<https://doi.org/10.51202/9783186952035-I>

Generiert durch IP '207.241.231.83' am 27.04.2021, 14:37:39

Das Erstellen und Weitergeben von Kopien dieses PDFs ist nicht zulässig.



# Reactor Network Synthesis With Guaranteed Robust Performance

Synthese von Reaktornetzwerken mit robust garantierten Eigenschaften

Von der Fakultät für Maschinenwesen der Rheinisch-Westfälischen Technischen  
Hochschule Aachen vorgelegte Dissertation zur Erlangung des akademischen Grades eines  
Doktors der Ingenieurwissenschaften

vorgelegt von

Xiao Zhao  
aus  
Xinjiang, China

Berichter: Universitätsprofessor Dr.-Ing. Wolfgang Marquardt  
Universitätsprofessor Dr.-Ing. Martin Mönnigmann

Tag der mündlichen Prüfung: 18.05.2017

D82 (Diss. RWTH Aachen University)



# Fortschritt-Berichte VDI

Reihe 3

Verfahrenstechnik

M.Sc. Xiao Zhao,  
Xinjiang

Nr. 952

Reactor network  
synthesis with  
guaranteed robust  
performance

Berichte aus der  
Aachener Verfahrenstechnik - Prozesstechnik

RWTH Aachen University



Zhao, Xiao

## **Reactor network synthesis with guaranteed robust performance**

Fortschr.-Ber. VDI Reihe 3 Nr. 952. Düsseldorf: VDI Verlag 2017.

184 Seiten, 24 Bilder, 19 Tabellen.

ISBN 978-3-18-395203-8, ISSN 0178-9503,

€ 67,00/VDI-Mitgliederpreis € 60,30.

**Für die Dokumentation:** Reactor network synthesis, Integration of process and control system design, Superstructure approach, Eigenvalue constraints, Mixed-integer nonlinear programming, Normal vector approach, Robust optimization

In this work a systematic model-based approach for reactor network synthesis problem with guaranteed robust dynamic performance will be presented. The work is based on the superstructure approach and aims to find an optimal process flowsheet with determined connection patterns of reactors, reactor types, design parameters and operating conditions. In comparison to the classical design methods, certain specified dynamic properties are guaranteed simultaneously under parametric uncertainty. Structural alternatives in the flowsheet, i.e., how reactors are interconnected, as well as in the control system, i.e., how controlled and manipulated variables are paired, are subject to design degrees of freedom. It is allowed that idle reactors and controllers can appear in the reactor network superstructure, so that a fixed number of non-idle reactors and controllers does not have to be assumed a priori. The optimal reactor network design in either open- or closed-loop is determined by solving a single optimization problem.

### **Bibliographische Information der Deutschen Bibliothek**

Die Deutsche Bibliothek verzeichnet diese Publikation in der Deutschen Nationalbibliographie; detaillierte bibliographische Daten sind im Internet unter <http://dnb.ddb.de> abrufbar.

### **Bibliographic information published by the Deutsche Bibliothek**

(German National Library)

The Deutsche Bibliothek lists this publication in the Deutsche Nationalbibliographie (German National Bibliography); detailed bibliographic data is available via Internet at <http://dnb.ddb.de>.

D82 (Diss. RWTH Aachen University, 2017)

© VDI Verlag GmbH · Düsseldorf 2017

Alle Rechte, auch das des auszugsweisen Nachdruckes, der auszugsweisen oder vollständigen Wiedergabe (Fotokopie, Mikrokopie), der Speicherung in Datenverarbeitungsanlagen, im Internet und das der Übersetzung, vorbehalten.

Als Manuskript gedruckt. Printed in Germany.

ISSN 0178-9503

ISBN 978-3-18-395203-8

<https://doi.org/10.51202/9783186952035-1>

Generiert durch IP '207.241.231.83', am 27.04.2021, 14:37:39.

Das Erstellen und Weitergeben von Kopien dieses PDFs ist nicht zulässig.

---

# Acknowledgements

The present thesis originates from my study and work time at Aachener Verfahrenstechnik, Process Systems Engineering at RWTH Aachen University as scientific staff.

I would like to express my deep and sincere gratitude to my thesis advisor Prof. Dr.-Ing. Wolfgang Marquardt. His thoughtful guidance, his valuable suggestions, his encouragements and his open mind to new ideas are the essential prerequisites of finishing this thesis. I also wish to express my warm and sincere thanks to Prof. Dr.-Ing. Martin Mönningmann for reviewing my thesis and Prof. Dr.-Ing. Uwe Reisgen to be the chairman of exam commission.

I would like to thank all the colleagues at the institute for the friendly and cooperative atmosphere. I am particularly thankful to Diego A. Muñoz for his great help during my starting phase; Maxim Stuckert, Ralf Hannemann, Yi Heng und Ionut Muntean for the fruitful discussions on mathematics, Sebastian Recker and Mirko Skiborowski for their important support in process modeling. At the end, I would like to thank Moritz Schmitz, Michael Wiedau, Nimet Kerimoglu, Ganzhou Wang, Matthias Johannink and Klaus Stockmann for the good time working together in the same office.

Finally, I owe my loving thanks to my wife Rui and my daughter Meitang for their love and support. I would also like to thank my parents for their love and continuous support.

Aachen, in May 2017



---

# Contents

<b>Notation</b>	<b>VIII</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Reactor network synthesis	1
1.1.1 Motivation	1
1.1.2 Task	1
1.1.3 Methods	2
1.2 Design of decentralized control systems	3
1.2.1 Tasks	4
1.2.2 Methods	5
1.3 Simultaneous process and control system design	7
1.3.1 Motivation	7
1.3.2 Methods	8
1.4 Content and goals of this work	10
1.4.1 Overview	10
1.4.2 New features of this work	14
<b>2 Some Preliminaries</b>	<b>17</b>
2.1 Dynamic systems	17
2.2 Eigenvalue and spectral abscissa functions	19
2.3 Lyapunov stability	23
2.4 Dynamic response	25
2.5 Extension to differential-algebraic systems	28
<b>3 Open-loop reactor network synthesis</b>	<b>30</b>
3.1 Structured modeling of reactor networks	30
3.1.1 A structured representation of reactor network models	31
3.1.2 Models of Subsystem 1 to $N$	34
3.1.3 Models of subsystems $N + 1$ and $N + 2$	36
3.1.4 Modeling flow connections	37
3.1.5 A dynamic model of the network	38
3.1.6 Idle reactors in open-loop reactor networks	39
3.2 Problem formulation	40
3.2.1 Eigenvalue constraint for open-loop reactor network synthesis	40
3.2.2 Continuity analysis of the proposed eigenvalue constraint	41
3.2.3 A direct problem formulation	43
3.2.4 Problem reformulation	44
3.3 Summary	46
<b>4 Simultaneous design of reactor network and its decentralized control system</b>	<b>47</b>

4.1	Modeling of reactor networks with decentralized control structure . . . . .	47
4.1.1	A closed-loop reactor network model . . . . .	47
4.1.2	Complementarity constraints for control structure selection . . . . .	50
4.1.3	Idle reactors and controllers . . . . .	51
4.1.4	Structural constraints . . . . .	53
4.1.5	Structural properties of the closed-loop model . . . . .	54
4.2	Problem formulation . . . . .	55
4.2.1	Eigenvalue constraint for simultaneous reactor network and control system synthesis . . . . .	56
4.2.2	Problem formulation . . . . .	57
4.3	Summary . . . . .	58
<b>5</b>	<b>Solution methods</b>	<b>60</b>
5.1	Discrete-continuous optimization . . . . .	60
5.1.1	Mixed-integer nonlinear program . . . . .	60
5.1.2	General concepts to solve MINLP . . . . .	60
5.1.3	Solution methods for convex MINLP . . . . .	61
5.1.4	Solution methods for non-convex MINLP . . . . .	62
5.1.5	Generalized disjunctive programming . . . . .	63
5.2	Mathematical programs with complementarity constraints . . . . .	64
5.2.1	MPCC versus NLP . . . . .	65
5.2.2	Solution methods for MPCC . . . . .	67
5.2.3	Relationship to MINLP . . . . .	71
5.3	Semi-infinite programming . . . . .	72
5.3.1	Local solution methods for SIP . . . . .	73
5.3.2	Global solution methods for SIP . . . . .	79
5.3.3	A robust design method: Normal vector approach . . . . .	82
5.4	Eigenvalue optimization . . . . .	89
5.4.1	Relation to semi-definite programming . . . . .	90
5.4.2	Solution methods for EVO: Non-smooth optimization . . . . .	91
5.4.3	Solution methods for EVO: Smoothing techniques . . . . .	94
5.5	Challenges of solving the derived reactor network synthesis problem . . . . .	99
5.6	A proposed two-step hybrid solution method . . . . .	100
5.6.1	Step 1: Mixed-integer problem without uncertainty . . . . .	101
5.6.2	Step 2: Robust optimization problem . . . . .	102
5.7	Implementation . . . . .	104
<b>6</b>	<b>Case study of allyl chloride production</b>	<b>107</b>
6.1	Open-loop reactor network design with robust stability . . . . .	107
6.1.1	Problem setting . . . . .	107
6.1.2	Design results . . . . .	110
6.2	Simultaneous reactor network and control system design for fast response . . . . .	120
6.2.1	Closed-loop reactor network modeling . . . . .	120
6.2.2	Problem setting . . . . .	122
6.2.3	Results and discussion . . . . .	123
6.2.4	Comparison with established sequential design . . . . .	127
6.3	Computational experience . . . . .	130

<b>7 Summary and outlook</b>	<b>133</b>
7.1 Contributions and summary of this work . . . . .	133
7.2 Future research directions . . . . .	135
7.2.1 Extensions regarding to the guaranteed robust dynamic properties .	135
7.2.2 Extensions regarding optimization methods . . . . .	136
7.2.3 Extension to control structure selection for linear system . . . . .	137
7.2.4 Other possible extensions and improvements . . . . .	139
<b>Appendices</b>	<b>141</b>
<b>A Extension of the reactor network model to PFR</b>	<b>142</b>
<b>B Proof of Proposition 3.2.1</b>	<b>145</b>
<b>C Proof of Proposition 3.2.2</b>	<b>148</b>
<b>D Parametric optimization problems</b>	<b>149</b>
<b>E Proof of Theorem 5.3.10</b>	<b>151</b>
<b>Bibliography</b>	<b>158</b>

---

## Notation

We summarize the symbols for reactor network modeling and the derived problem formulations in Chapter 3 and 4. The symbols for the introduction part of nonlinear systems in Chapter 2 and the symbols for reviewing different numerical optimization methods shown in Chapter 5 are not presented here. The meaning of these symbols is always introduced together with the corresponding texts.

## Symbols for the reaction example

$A$	propylene
$B$	allyl chloride
$C$	chlorine
$c_A, c_B, c_C$	concentration of component $A$ , $B$ or $C$
$R$	gas constant
$a_1, a_2, a_3$	reaction constants
$H_1, H_2, H_3$	heat of reaction per mol
$c_p$	heat capacity
$T$	temperature
$V$	reactor volume
$L$	reactor length
$r_1, r_2, r_3$	reaction rates
$R_A, R_B, R_C$	reaction rates for component $A$ , $B$ , $C$
$\dot{n}_A^0, \dot{n}_B^0, \dot{n}_C^0$	mole flowrates of inlets
$\dot{Q}^0$	energy flowrate of inlets
$Q_h$	energy duty of heat exchanger
$c_A^{sys}, c_B^{sys}, c_C^{sys}$	concentration in system's inlet
$E^{sys}$	energy density in system's inlet
$N_d$	number of discretized points of each PFR

## Symbols for open-loop reactor network design

$i$	index of subsystems
$j$	index of outlet ports
$k$	index of inlet ports
$N$	total number of reactors
$(i, j)$	index of the $j$ -th outlet port of subsystem $i$
$(i, k)$	index of the $k$ -th inlet port of subsystem $i$
$l(i, j)$	index of an inlet port, which is connected to $(i, j)$
$h(i, k)$	index of an outlet port, which is connected to $(i, k)$

$(i, j) \triangleright (i', k')$	pipe connection from $(i, j)$ to $(i', k')$
$\bar{l}(i, j)$	index of a subsystem, one of its inlets is connected to $(i, j)$
$\bar{h}(i, k)$	index of a subsystem, one of its outlets is connected to $(i, k)$
$N_c$	number of necessary chemical components to model reactions
$x_i$	states (concentrations, temperature) of reactor $i$
$u_{i,k}$	component flowrates and energy flowrate through inlet port $(i, k)$
$q_{i,j}$	volumetric flowrate through the $(i, j)$ -th outlet port
$p_i$	design parameters of reactor $i$
$f_i(\cdot)$	function for mass and energy balances of reactor $i$
$y_{i,j}$	component flowrates and energy flowrate through outlet port $(i, j)$
$g_{i,j}(\cdot)$	function for reactor's outlets
$y_{sys}$	component flowrates and energy flowrate in system's outlet
$p_{sys}$	molar concentration and energy density in the system's feed
$\mathcal{I}$	index set of all reactors
$\mathcal{I}_{id}$	index set of idle reactors
$\mathcal{I}_{nid}$	index set of non-idle reactors
$J_{tot}$	Jacobian matrix of the open-loop reactor network
$J_{id}$	Jacobian matrix of idle reactors
$J_{nid}$	Jacobian matrix of non-idle reactors
$\bar{J}$	a constructed matrix
$c$	predefined constant for the upper bound of eigenvalue constraints
$\alpha(\cdot)$	spectral abscissa function
$D_o$	definition domain of function $\alpha_{J_{nid}}(\cdot)$
$P^*$	steady state of the 2-reactor network example
$\varphi$	objective function in optimization
$\pi_\tau$	vector of uncertain variables
$\bar{\pi}_\tau$	nominal values of uncertain variables
$\Delta\bar{\pi}_\tau$	uncertain range of uncertain variables
$z_i$	integer for the existence of reactor $i$
$z$	a vector of $z_i$ , $i = 1, \dots, N$
$M$	sufficiently large positive constant in big-M method
$I$	identity matrix
$\psi_o$	degrees of freedom of the open-loop model
$\epsilon$	a small positive number

## Symbols for simultaneous reactor network design and control

$u$	candidate MV of reactor network
$y$	candidate CV of reactor network
$e$	state variables of PI controllers
$\bar{u}$	offset values of $u$
$\bar{y}$	reference signals of $y$
$\bar{q}$	offset values of $q$
$u_i$	candidate MV of reactor $i$ (elements of $p_i$ )
$d_i$	equipment design parameters of reactor $i$ (elements of $p_i$ )

$u_{p1}$	candidate MV, which belong to idle reactors
$u_{p2}$	candidate MV, which do not belong to idle reactors
$n_c$	dimension of $y$ , i.e. total number of candidate CV
$n_m$	dimension of $u$ , i.e. total number of candidate MV
$(i, r)$	index of the $r$ -th candidate measurement of reactor $i$
$n_c^i$	index of the $(i, r)$ -th candidate PI controller
$e_{i,r}$	dimension of all candidate CV of reactor $i$
$\pi$	state variable of $(i, r)$ -th PI controller
$v$	variables in $\psi_o$ , which are not in $u$
	location index for candidate MV
	location index for rows of control gain matrix $K$
$w$	location index for candidate CV
	location index for columns of control gain matrix $K$
$[u]_v$	$v$ -th element in vector $u$
$[y]_m$	$m$ -th element in vector $y$
$\Theta_i$	index set for candidate MV of reactor $i$
$y_{i,r}$	$r$ -th candidate CV of reactor $i$
$\phi_{i,r}(\cdot)$	function for candidate CV
$\rho(\cdot, \cdot)$	function for transforming the subscripts of $[y]_m$ and $y_{(i,r)}$
$K$	proportional control gain matrix
$[K]_{v,w}$	$(v, w)$ -th element in matrix $K$
$K_v$	vector of variables in matrix $K$
$K^+, K^-, \hat{K}$	auxiliary matrices for control structure selection
$T$	integral control gain matrix
$t_{i,r}$	integral control gain for state $e_{i,r}$
$T_v$	vector of variables in matrix $T$
$\psi_c$	degrees of freedom of the closed-loop model
$\mathcal{U}$	index set of all candidate MV
$\mathcal{U}_{id}$	index set of candidate MV, which are not subject to control
$\mathcal{U}_{nid}$	index set of candidate MV, which are subject to control
$\mathcal{C}$	index set of all PI controllers
$\mathcal{C}_{id}$	index set of idle PI controllers
$\mathcal{C}_{nid}$	index set of non-idle PI controllers
$z_{i,r}$	integer for the existence of the $(i, r)$ -th PI controller
$z_r$	a vector of $z_i$ (existence of reactors)
$z_c$	a vector of $z_{i,r}$ (existence of controllers)
$x_{id}$	states of idle reactors
$x_{nid}$	states of non-idle reactors
$e_{id}$	states of idle controllers
$e_{nid}$	states of non-idle controllers
$J_{tot}$	Jacobian matrix of the closed-loop reactor network model
$J_{id}, J'_{id}, J_{nid}, J'_{nid}$	Submatrices in $J_{tot}$
$F_{id}(\cdot)$	state functions of all idle reactors and controllers
$F_{nid}(\cdot)$	state functions of all non-idle reactors and controllers
$\bar{J}$	a constructed matrix

## Mathematical notations

$\mathbb{R}$	real line
$\mathbb{R}^n$	real n-dimensional space
$\mathbb{R}_+^n$	non-negative orthant of $\mathbb{R}^n$
$\mathbb{C}$	complex plane
$\mathcal{C}^k$	space of $k$ -th order continuously differentiable functions
$\frac{\partial f}{\partial x}$	partial derivatives of function $f(x)$ to $x$
$\bar{B}$	topological closure of a set $B$

## Acronyms

NLP	nonlinear optimization
MINLP	mixed-integer nonlinear optimization
MILP	mixed-integer linear optimization
MIDO	mixed-integer dynamic optimization
GDP	generalized disjunctive programming
MPCC	mathematical programs with complementarity constraints
MPEC	mathematical programs with equilibrium constraints
SIP	semi-infinite programming
GSIP	generalized semi-infinite programming
EVO	eigenvalue optimization
SDP	semi-definite programming
NSO	non-smooth optimization
DOF	degrees of freedom
SA	spectral abscissa
NVA	normal vector approach
CV	controlled variable
MV	manipulated variable
B&B	branch and bound (with respect to binary variables)
sB&B	spatial branch and bound
GBD	generalized bender's decomposition
VI	variational inequalities
MFCQ	Mangasarian Fromovitz constraint qualification
LICQ	linear independence constraint qualification
KKT	Karush Kuhn Tucker
SQP	sequential quadratic programming
NCP	nonlinear complementary problem
FB	Fischer-Burmeister
BL	bi-level
EPF	elementary process functions
AR	attainable region
PI	proportional-integral
RGA	relative gain array
SV	singular values

NI	Niederlinski index
SSV	structured singular value
MIMO	multi-input multi-output
ODE	ordinary differential equations
DAE	differential algebraic equations

---

## Abstract

Typical continuous process flowsheets include reaction section, separation section and recycles. The reaction section is often the most important part of a chemical process, which may contain several interconnected reactors. The superstructure approach is a widely used model-based process design method for reactor network synthesis. It starts from a reactor network superstructure and uses mathematical models and optimization tools to select the best process design. The superstructure approach results in an optimal process flowsheet with determined connection patterns of reactors, reactor types, design parameters and operating conditions of each reactor.

In this work, a systematic model-based approach for reactor network synthesis problems with guaranteed robust dynamic performance will be presented. The work is based on the superstructure approach, but in comparison to the classical methods, not only economic optimality with respect to a static objective function, but also certain specified dynamic properties, i.e. dynamic stability and response speed, are guaranteed simultaneously under parametric uncertainty. Structural alternatives in the flowsheet, i.e., how reactors are interconnected, as well as in the control system, i.e., how controlled and manipulated variables are paired, are subject to design degrees of freedom. Moreover, it is allowed that idle reactors and controllers can appear in the reactor network superstructure, so that a fixed number of non-idle reactors and controllers does not have to be assumed a priori. The optimal reactor network design in either open- or closed-loop is determined by solving a single optimization problem.

The proposed approach allows an integrated treatment of parametric uncertainties, which may either result from model uncertainties, such as reaction kinetic constants or heat transfer coefficients, or from process uncertainties, including slow disturbances in load or the quality of raw materials. A robust eigenvalue constraint to guarantee the robust performance of the designed reactor network is formulated. Efficient formulations of interconnecting reactors and novel complementarity-based constraints for control structure selection are proposed. The method results in a semi-infinite mixed-integer nonlinear optimization problem with complementarity constraints, disjunctions and a robust eigenvalue constraint. A hybrid two-step solution method is proposed to solve the synthesis problem, which integrates candidate solution algorithms of related optimization problems. The proposed solution method is applied to a case study of allyl chloride production with up to ten plug flow and continuous stirred tank reactors.

---

# Kurzfassung

Übliche kontinuierliche Prozesse enthalten einen Reaktionsteil, eine Trennsequenz und Rückführungen. Der Reaktionsteil stellt meist den wichtigsten Teil eines chemischen Prozesses dar, der aus vielen untereinander verknüpften Reaktoren bestehen kann. Der Überstrukturansatz beschreibt eine oft genutzte, modellgestützte Methode zur Erstellung von Reaktornetzwerken mit strukturellen Freiheitsgraden. Ausgehend von einer Überstruktur des Reaktornetzwerkes werden mathematische Modelle und Optimierungswerkzeuge genutzt, um den besten Prozessentwurf zu finden. Der Überstrukturansatz resultiert in einem optimalen Prozessfließbild mit festgelegten Verknüpfungen der Reaktoren eines bestimmten Reaktortyps sowie mit den zugehörigen Designparametern und Betriebsbedingungen für jeden Reaktor.

In dieser Arbeit wird ein systematischer, modellgestützter Ansatz für den Entwurf von Reaktornetzwerken mit garantiert robusten dynamischen Eigenschaften präsentiert. Die Arbeit basiert auf dem Überstrukturansatz. Im Vergleich zu konventionellen Methoden wird jedoch nicht nur die ökonomische Optimalität in Bezug auf eine statische Zielfunktion, sondern auch bestimmte spezifische dynamische Eigenschaften, insbesondere die dynamische Stabilität und die Geschwindigkeit des Responses, gleichzeitig unter parametrischer Unsicherheit garantiert. Strukturelle Fließbildalternativen, insbesondere die Verknüpfung von Reaktoren untereinander und Alternativen in Bezug auf die Regelungsstruktur, d.h. insbesondere die Kopplung von geregelten und manipulierten Variablen, zählen zu den Freiheitsgraden des Entwurfsprozesses. Des Weiteren werden unbenutzte Reaktoren und Regler im Netzwerk zugelassen, sodass a-priori keine feste Anzahl von benutzten Reaktoren und Reglern vorgegeben werden muss. Der optimale Entwurf des Reaktornetzwerkes im offenen oder geschlossenen Regelkreis wird durch die Lösung eines einzelnen Optimierungsproblems ermittelt.

Der vorgeschlagene Ansatz erlaubt eine integrierte Behandlung von parametrischen Unsicherheiten, die entweder aus Modellunsicherheiten resultieren, wie z.B. Konstanten in der Reaktionskinetik oder Wärmeübergangskoeffizienten, oder aus Prozessunsicherheiten, die auch langsame Veränderungen des Zuflusses oder der Qualität der Edukte einschließen. Es wird eine robuste Zwangsbedingung für die Eigenwerte formuliert, um ein robustes Verhalten des entworfenen Reaktornetzwerkes zu garantieren. Effiziente Formulierungen zur Verknüpfung von Reaktoren und neue Zwangsbedingungen zur Auswahl der Regelungsstruktur, die auf Komplementarität basieren, werden vorgeschlagen. Die Methode resultiert in einem semi-infiniten gemischt-ganzzahligen nichtlinearen Optimierungsproblem mit Komplementaritätsbedingungen, Disjunktionen, und einer robusten Eigenwert-Nebenbedingung. Es wird eine hybride zweistufige Lösungsmethode vorgeschlagen, welche die Lösungsalgorithmen des verwandten Optimierungsproblems integriert. Die vorgeschlagene Lösungsmethode wird auf eine Fallstudie der Allylchlorid-Produktion mit bis zu zehn Rohrreaktoren bzw. Rührkesselreaktoren angewandt.